



RoHS COMPLIANT

REV	ECN NO.	DESCRIPTION	DATE
A		RELEASE	MAY. 12'03
B		REDRAW	DEC. 12'07
C		MODIFY P/N	JAN. 25'11

SPECIFICATIONS

- Voltage Rating : 250V AC/DC
- Current Rating : 3A AC/DC
- Withstanding Voltage : 1000V AC/minute
- Insulation Resistance : 1000MΩ min
- Temperature Range : - 25°C to + 85°C
- Contact Resistance : 20mΩ max

TERMINAL

- Applicable Wires : AWG # 24 - 28
- Material : Brass, Phos. Bronze
- Finish : Tin Plated
- Thickness : 0.2 mm
- Q' ty : 10000 pcs./Reel

A-A SEC

B-B SEC

C-C SEC

TOLERANCE UNLESS OTHERWISE SPECIFIED		PROJECTION	GOLD-TEK ELECTRIC CO., LTD.											
<table border="1"> <thead> <tr> <th>LINEAR</th> <th>ANGLE</th> </tr> </thead> <tbody> <tr> <td>X. ±</td> <td>X° ±</td> </tr> <tr> <td>.X ± 0.30</td> <td>.X° ±</td> </tr> <tr> <td>.XX ± 0.20</td> <td>.XX° ±</td> </tr> <tr> <td>.XXX±</td> <td>.XXX° ±</td> </tr> </tbody> </table>		LINEAR	ANGLE	X. ±	X° ±	.X ± 0.30	.X° ±	.XX ± 0.20	.XX° ±	.XXX±	.XXX° ±		GOLD-TEK ELECTRIC CO., LTD.	
LINEAR	ANGLE													
X. ±	X° ±													
.X ± 0.30	.X° ±													
.XX ± 0.20	.XX° ±													
.XXX±	.XXX° ±													
APPD		UNITS	TITLE	PART NO.										
CHKD		MM	2.54MM TERMINAL	8001T										
DRAW	Z	SCALE	CPART NO.	CAD NO. 1056										
	JAN. 25'2011	SIZE		SHEET 1 OF 1										
		A4		圖面編號:GTKSD0004-C(1)										