



P. C. B LAND PATTERN

Specifications:  
 Rating:DC50V 1A  
 Force:5-35N  
 Contact resistance:  
 Less than30mΩ  
 Insulation resistance:  
 Over100MΩ on DC 500V measured.  
 Voltage withstand:  
 AC 500V For 1minute,



SCHEMATIC

13	SLEEVE	1	BRASS		MB: Ni, Au	
12	M TERMINAL-L	1	BRONZE	Y=0.25	MB: Cu, Ag	No. 9
11	M TERMINAL-R	1	BRONZE	Y=0.25	MB: Cu, Ag	No. 6
10	B TERMINAL-L	1	BRASS	Y=0.5	MB: Cu, Ag	No. 7
9	B TERMINAL-R	1	BRASS	Y=0.5	MB: Cu, Ag	No. 4
8	SEPARATOR	2	POM	94V2	BLACK	
7	T TERMINAL-L	1	BRONZE	Y=0.3	MB: Cu, Ag	No. 8
6	T TERMINAL-R	1	BRONZE	Y=0.3	MB: Cu, Ag	No. 5
5	RING TERMINAL	1	BRONZE	Y=0.25	MB: Cu, Ag	No. 3
4	TIP SPPING	1	BRONZE	Y=0.25	MB: Cu, Ag	No. 2
3	EARTH SPPING	1	BRONZE	Y=0.25	MB: Cu, Ag	No. 1
2	COVER	1	PC	94HB	WHITE	
1	HOUSING	1	ABS	94HB	BLACK	

LTR	PART NAME	QTY	MATERIAL	FINISH	REMARK
	TOLERANCE				
	X . X				±0.3
	X . X X				±0.2
	X . X X X				±0.1
	ANGLE				±3.0°
	SCALE 2/1				NWE PHONE JACK
	UNIT: mm				CAT. NO. CK-6306