


HIGH VOLTAGE APPLICATION.

FEATURE

- Complementary to KTC1027.

MAXIMUM RATING (Ta=25°C)

| CHARACTERISTIC | SYMBOL | RATING | UNIT |
|-----------------------------|-----------|-----------|------|
| Collector-Base Voltage | V_{CBO} | -120 | V |
| Collector-Emitter Voltage | V_{CEO} | -120 | V |
| Emitter-Base Voltage | V_{EBO} | -5 | V |
| Collector Current | I_C | -800 | mA |
| Emitter Current | I_E | 800 | mA |
| Collector Power Dissipation | P_C | 1 | W |
| Junction Temperature | T_j | 150 | °C |
| Storage Temperature Range | T_{stg} | -55 ~ 150 | °C |




ELECTRICAL CHARACTERISTICS (Ta=25°C)


| CHARACTERISTIC | SYMBOL | TEST CONDITION | MIN. | TYP. | MAX. | UNIT |
|--------------------------------------|-----------------------|------------------------------|------|------|------|------|
| Collector Cut-off Current | I_{CBO} | $V_{CB}=-120V, I_E=0$ | - | - | -100 | nA |
| Emitter Cut-off Current | I_{EBO} | $V_{EB}=-5V, I_C=0$ | - | - | -100 | nA |
| Collector-Emitter Saturation Voltage | $V_{(BR)CEO}$ | $I_C=-10mA, I_B=0$ | -120 | - | - | V |
| Emitter-Base Breakdown Voltage | $V_{(BR)EBO}$ | $I_E=-1mA, I_C=0$ | -5 | - | - | V |
| DC Current Gain | $h_{FE}(\text{Note})$ | $V_{CE}=-5V, I_C=-100mA$ | 80 | - | 240 | |
| Collector-Emitter Saturation Voltage | $V_{CE(sat)}$ | $I_C=-500mA, I_B=-50mA$ | - | - | -1.0 | V |
| Base-Emitter Voltage | V_{BE} | $V_{CE}=-5V, I_C=-500mA$ | - | - | -1.0 | V |
| Transition Frequency | f_T | $V_{CE}=-5V, I_C=-100mA$ | - | 120 | - | MHz |
| Collector Output Capacitance | C_{ob} | $V_{CB}=-10V, I_E=0, f=1MHz$ | - | - | 40 | pF |

Note : h_{FE} Classification O:80 ~ 160, Y:120 ~ 240


$I_C - V_{CE}$




$h_{FE} - I_C$




$V_{CE(sat)} - I_C$



$I_C - V_{BE}$



$P_C - T_a$



AREA OF SAFE OPERATION

