

Approval Specification Sheet



**HONG KONG
X'TALS LIMITED**

Unit L-M, 24/F., Shield Industrial Centre,
84-92 Chai Wan Kok Street,
Tsuen Wan, N.T., Hong Kong.
Tel : (852) 35112388
Fax : (852) 35112420
Web : <http://www.hongkongcrystal.com>

End User			
Company	Electronics Source Co., Ltd.		
Sales Rep.		Project	
Attention	Ms ZaZa	Date	April 21, 2009
Phone	662-884-9210 ext. 141	Fax	662-884-9213
Yr Ref. No.		Our Ref.	

Prod. Code	CHM14318MSES08J01-0
Nominal Frequency	14.318 MHz
Holder Type	Clock oscillator Half size dip type
Frequency Tolerance	± 50 ppm / -20 °C TO 80 °C
Storage Temperature Range	- 40°C TO 85°C
Power Supply Voltage	5V ± 10%
Current Consumption	35mA
Rise and Fall Time	Tr / Tf < 10nS
Output Level	CMOS
Symmetry	40 ~ 60% @50% VDC
"0" Voltage	< 10% VDC
"1" Voltage	> 90% VDC
Output Load	50pF
Tri-state Option	No
Marking	MEC+14.318MHZ+. MO-22B-{Y/M}

Options

- | | |
|--|---|
| <input type="checkbox"/> Centre Ground Lead
<input type="checkbox"/> Ground Lead at Top
<input type="checkbox"/> Non-standard lead length
<input checked="" type="checkbox"/> Tube
<input type="checkbox"/> Blister Tape | <input type="checkbox"/> Spacer / Insulator
<input type="checkbox"/> Sleeve
<input type="checkbox"/> Bent Lead
<input type="checkbox"/> Laser Marking
<input checked="" type="checkbox"/> Ink/Laser Marking |
|--|---|

Detail Dimensions Please Refer to :

Technical Drawing # :

Packing Drawing # :

Remarks for Customer Specifications :

Customer Part No. OSC-14.318M-H-LF

Remarks LEAD FREE

Hong Kong X'tals Limited		Comments:
Issued by		
Inspected by		
Approved by		
		Approved By Customer : _____