

规格型号Specification		2464 24AWG/6C+A		示意图Cross-Sectional View					
环保ROHS/REACH		√		客户编号Customer number					
项目ITEM		技术参数 Technical parameter							
导体CONDUCTOR	规格AWG	24AWG							
	材质MATERIAL	镀锡铜 Tinned copper							
	结构COND SIZE	11/0.16±0.008 MM							
绝缘INSULATION	材质MATERIAL	PVC							
	厚度 AVERAGE THICKNESS	0.31MM							
	外径OD	1.25±0.05MM							
	芯数CORE NUMBER	6 C							
屏蔽SHIELDING	材质MATERIAL	铝箔（导电面朝内） Aluminum Foil(Metal Face in)		绝缘颜色INSULATION COLOUR					
	结构COND SIZE	/		Red, Yellow, Green, Blue, Black, and White					
	覆盖率Shielding Ratio	100%							
护套SHEATING	厚度 AVERAGE THICKNESS	0.78MM							
	材质MATERIAL	PVC							
	颜色COLOUR	灰色 Grey							
	外径OD	5.40±0.10MM							
				印字内容MARKING					
				兄 AWM 2464 E330484 VW-1 80°C 300V 24AWG B&T CABLE c兄 AWM I A FT1 80°C 300V 24AWG -LF-					
				印字颜色MARKING COLOUR					
性能CHARACTERISTICS				黑色 Black					
1.耐温等级WITHSTAND TEMP: 80°C 2.耐压等级WITHSTAND VOLTAGE: 300V		Packing:100Meter/Roll		版本 Version	日期DATA	更改者Changers			
				BORT®					
				参考标准Reference Standard	批准APPROVED	Romen	客户Customer		
				客人要求	检查CHECKED	DAVID	版本Version	A0	
					设计DRAWING	Andy	日期DATA	2023/7/14	
			产品编号 PART NO	BT246406241103	规格书编号 Datasheet NO	C001-XXXXXX			